

# MC5000



## MERU MC5000 CONTROLLER

The Meru MC5000 Series Controller, supporting up to 1,500 access points and 20Gbps encrypted throughput, provides a flexible and dynamically scalable solution.



### EXTENDIBLE & MODULAR CONTROLLER

Simplicity, versatility, and reliability to meet your operational needs, scalability to virtualize even the largest enterprise WLAN

## PRODUCT OVERVIEW

The Meru MC5000 Series Controller, supporting up to 1,500 access points and 20Gbps encrypted throughput, provides a flexible and dynamically scalable solution with unprecedented reliability for large enterprises and branch offices.

This fully extendible, modular hardware system allows network administrators to securely manage and easily control their wireless network while meeting mission critical enterprise demands. As part of the Meru Networks controller family, the MC5000 provides centralized configuration and management for ease of deployment, multilayer security, N+1 redundancy and scalability while eliminating co-channel interference and the need for channel planning.

The MC5000 is E(z)RF™ Application Suite compliant and easily integrates with existing infrastructure.



**The MC5000 Controller** supports up to 1,500 access points and 20Gbps encrypted throughput.

# MC5000 TECHNICAL SPECIFICATIONS

## APPLICATION SUPPORT AND OVER-THE-AIR QoS

### SIP and H.323 support

Dynamic out of the box support for SIP and H.323v1 applications and codecs

### QoS

Configurable dynamic QoS rules Over-the-air resource reservation Automatic, stateful flow detectors for SIP, H.323, Cisco SCCP, SpectraLink SVP and Vocera User-configurable static and dynamic QoS rules per application (user-defined) and per user (stations, users, and port numbers) Call Admissions Control and Call Load Balancing WMM Support

## SECURITY

### Authentication

Combination of captive portal, 802.1x and open authentication Advanced security using WPA2 802.1X with EAP-Transport Layer Security (EAP-TLS), Tunneled TLS (EAP-TTLS), Protected EAP (PEAP) MS-CHAPv2, Smartcard/Certificate, Lightweight EAP (LEAP), EAP-FAST and EAP-MD5, with mutual authentication and dynamic, per user, per session unicast and broadcast keys Secure HTTPS w/customizable Captive Portal utilizing RADIUS

### Encryption support

Static and dynamic 40-bit and 128-bit WEP keys, TKIP with MIC, AES

### Security Policy

Radius Assisted, Per User and Per ESSID Access control via MAC Filtering Multiple ESSID/BSSID each with flexibility of separate and shared Security Policy

### Rogue Detection and Suppression

All radios capable of scanning 802.11n, 802.11a and 802.11b/g for rogue devices

### Security Firewall

10,000 simultaneous sessions System configured or Per User Radius configured firewall policy

## MOBILITY

**Zero-loss Handoffs** Infrastructure-controlled zero-loss handoff mechanism for standard Wi-Fi clients

**Virtual Cell Load Balancing** Virtual Cell provides load balancing coordination for improved performance and WLAN resiliency upon AP failure

## CENTRALIZED MANAGEMENT

### Zero-Configuration

Automatically selects power and channel settings Automatically discovers controllers and download configuration settings Zero touch, plug and play deployments

### System Management

Centralized and remote management and software upgrades via System Director web-based GUI, SNMP, Command-Line Interface (CLI) via serial port, SSH, Telnet, centrally managed via EzRF Management Suite Centralized Security Policy for WLAN, Multiple ESSIDs and VLANs with their own administrative/security policies

### Intelligent RF Management

Coordination of access points with load-balancing for predictable performance Centralized auto-discovery, auto-channel configuration, and auto-power selection for APs Co-channel interference management

## WIRED/WIRELESS SUPPORT

### Wireless Compliance

IEEE 802.11 a/b/g/n, IEEE 802.11i support (AES, WEP, WPA, WPA2), IEEE 802.11e, WMM

### Automatic Discovery & Configuration

All Meru Access Points

### Wired/Switching

IEEE 802.1Q VLAN tagging, GRE Tunneling and IEEE 802.1D Spanning Tree Protocol

## PHYSICAL SPECIFICATIONS

### Dimensions

19" width x 10 1/2" height x 15" depth (48.3 cm width x 26.7 cm height x 38.1 cm depth)

**Weight** 50-100 lbs (22.7-45 kg) depending on configuration

### Power Consumption

Per Blade: 200W Per Chassis: 1200W

### Environmental

Operating Temperature: 0° to 40° C (32° F to 104° F) Operating Humidity: 95% at 40° C (104° F) Storage Temperature: -40° to 85° C (-40° F to 185° F) Storage Humidity: 95% at 40° C (104° F)

### Interfaces

4 10/100/1000 Base-TX Ethernet or 2 Base-X SFP per blade; Max 5 blades per controller Power On/Off Switch Status Screen Ethernet Port Status Lights (LED) for Link/Activity/Speed Shelf Management Alarms for health status for each blade in the chassis

### Mounting

6U Rack Mount

### Standard Warranty

1 year

## Certifications

Wi-Fi Certified a/b/g/n

### Standards Safety

UL 60950-1 IEC 60950-1

### EMC

FCC Part 15/ICES-003 Class A VCCI Class A (Japan) EN 55022 (Europe) EN 55024 (Europe)

For other countries and regions, please contact your local Meru representative for more specific regulatory information.

**Meru Networks** | develops and markets wireless infrastructure solutions that enable the All-Wireless Enterprise. Its industry-leading innovations deliver pervasive, wireless service fidelity for business-critical applications to major Fortune 500 enterprises, universities, healthcare organizations and local, state and federal government agencies. Meru's award-winning Air Traffic Control technology brings the benefits of the cellular world to the wireless LAN environment, and its WLAN System is the only solution on the market that delivers predictable bandwidth and over-the-air quality of service with the reliability, scalability and security necessary to deliver converged voice and data services over a single WLAN infrastructure.

DS\_MC5000\_0310\_v5



Corporate Headquarters  
894 Ross Drive  
Sunnyvale, CA 94089  
T +1 (408) 215-5300  
F +1 (408) 215-5301  
E info@merunetworks.com

For more information about Meru AP150 visit | [www.merunetworks.com](http://www.merunetworks.com) | Or email your questions to: [info@merunetworks.com](mailto:info@merunetworks.com)

Meru Networks | Copyright © 2010 Meru Networks, Inc. All rights reserved worldwide. Meru Networks is a registered trademark of Meru Networks, Inc. in the US and worldwide. All other trademarks, trade names or service marks mentioned in this document are the property of their respective owners.